



# KRS Guide Wheel Bearing Co., Ltd

57,15 mm x 104,775 mm x 29,317 mm NTN  
4T-469/453X tapered roller bearings



Bearing No. 4T-469/453X

4T-469/453X Bearing 2D drawings and 3D CAD models

Size	57.15x104.775x30.162 mm
Bore Diameter	57,15 mm
Outer Diameter	104,775 mm
Width	30,162 mm
d	57,15 mm
D	104,775 mm
T	30,162 mm
B	29,317 mm
C	24,605 mm
ra1 max.	3,3 mm
a	7,1 mm
Da	92 mm
db	63 mm
ra max.	3,5 mm
da	70 mm
Db	98 mm
Weight	1,06 Kg
Basic dynamic load rating (C)	115 kN
Basic static load rating (C0)	148 kN
(Grease) Lubrication Speed	3 500 r/min
(Oil) Lubrication Speed	4 700 r/min
Calculation factor (e)	0,34
Calculation factor (Y0)	0,98
d1	79.5 mm
e	0.34



## KRS Guide Wheel Bearing Co., Ltd

Y2	1.79
Y0	0.98
Mass	1.06 kg
Dynamic load, C	115 kN
Rating life coefficient, A2	1.4
Static load, C0	148 kN
Fatigue limit load, Cu	18 kN
Nlim (oil)	4,700 rpm
Nlim (grease)	3,500 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.79 Hz
Characteristic outer ring frequency, BPF0	7.73 Hz
Characteristic inner ring frequency, BPF1	10.27 Hz
ra max	3.5 mm
r1a max	3.3 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.074
Product Group	B04334